This safety data sheet was created pursuant to the requirements of: Regulation (EC)



No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date 20/08/21 Revision Number 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name Carbusonic EPOXY PUTTY STICK

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Filler.
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Carbusonic LTD

11 Lynn terrace

Wheatley hill

Co Durham

DH6 3Qn

Tel: +44 07484265364

E-mail address info@carbusonic.co.uk

1.4. Emergency telephone number

United Kingdom +44 07484265364

(Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitisation	Category 1B - (H317)
Chronic aquatic toxicity	Category 3 - (H412)

2.2. Label Elements

Contains: Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW, Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2.2-bis(hydroxymethyl)1,3-propanediol (4:1), 2-hydroxy-3-mercaptop



Signal word Warning

Hazard statements

H315 - Causes skin irritation.

Revision date 20/8/21
Revision Number 1

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P273 - Avoid release to the environment.

P280 - Wear protective gloves and eye/face protection.

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention.

P501 - Dispose of contents/ container to an approved waste disposal plant.

2.3. Other Hazards

No information available

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

32 Mixtures

Chemical name	EC No.	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]		REACH Registration Number
Bisphenol-A-Epichlorhyd rin Epoxy resin <= 700 MW	500-033-5	25068-38-6	10 - <20	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Aquatic Chronic 2 (H411)	Eye Irrit. 2 :: C>=5% Skin Irrit. 2 :: C>=5%	
Poly[oxy(methyl-1,2-etha nediyl)], a-hydro-w-hydroxy-, ether with 2.2-bis(hydroxymethyl)1, 3-propanediol (4:1), 2-hydroxy-3-mercaptop	-	72244-98-5	10 - <20	Skin Sens. 1B (H317) Aquatic Chronic 3 (H412)		Exempt

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EPOXY PUTTY CARBUSONIC LIMITED Revision date 20/8/2021 **Revision Number** 1

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist. Do not rub affected area. Get medical

attention if irritation develops and persists.

May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see Skin contact

a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes.

Ingestion Clean mouth with water and drink afterwards plenty of water. Never give anything by

mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Itching. Rashes. Hives. Burning sensation.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Unsuitable extinguishing media Full water jet. Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

Specific hazards arising from the Product is or contains a sensitiser. May cause sensitisation by skin contact.

chemical

Carbon dioxide (CO2), Carbon monoxide, Oxides of sulphur, Hazardous metal fumes

and oxides.

5.3. Advice for firefighters

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal

protective equipment as required. Evacuate personnel to safe areas. Keep people away

from and upwind of spill/leak.

Other information Refer to protective measures listed in Sections 7 and 8.

EPOXY PUTTYCARBUSONIC LIMITED

Revision date 20/8/2021 Revision Number 1

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so.

6.3. Methods and material for containment and cleaning up

Methods for containment

Use a non-combustible material like vermiculite, sand or earth to soak up the product

and place into a container for later disposal.

Methods for cleaning upTake up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact

with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product.

Take off contaminated clothing and wash it before reuse.

General hygiene considerations Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using

this product. Avoid contact with skin, eyes or clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Keep out of the reach of children.

7.3. Specific end use(s)

Specific Use(s)

. Filler.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits This product, as supplied, does not contain any hazardous materials with occupational

exposure limits established by the region specific regulatory bodies

Chemical name	European Union	Ireland	United Kingdom
Talc	-	TWA: 10 mg/m ³	TWA: 1 mg/m ³
14807-96-6		TWA: 0.8 mg/m ³	STEL: 3 mg/m³
		STEL: 30 mg/m³ STEL: 2.4 mg/m³	

Derived No Effect Level (DNEL) No information available

EPOXY PUTTYCARBUSONIC LIMITED

Revision date 20/8/2021 Revision Number 1

Derived No Effect Level (DN	Derived No Effect Level (DNEL)			
Bisphenol-A-Epichlorhydrin	Epoxy resin <= 700 MW (25	5068-38-6)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Short term Systemic health effects	Dermal	8.33 mg/kg bw/d		
worker Long term Systemic health effects	Dermal	8.33 mg/kg bw/d		
worker Short term Systemic health effects	Inhalation	12.25 mg/kg bw/d		

Derived No Effect Level (DNEL)			
Bisphenol-A-Epichlorhydrin	Epoxy resin <= 700 MW (25	5068-38-6)	
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Short term Systemic health effects	Oral	0.75 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.75 mg/kg bw/d	

 $\begin{tabular}{ll} \textbf{Predicted No Effect Concentration} & \textbf{No information available.} \\ \textbf{(PNEC)} \end{tabular}$

Predicted No Effect Concentration (PNEC)			
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)			
Environmental compartment	Predicted No Effect Concentration (PNEC)		
Freshwater	0.006 mg/l		
Marine water	0.0006 mg/l		
Freshwater sediment	0.996 mg/l		
Marine sediment	0.0996 mg/l		
Soil	0.196 mg/l		

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the

breakthrough time of the glove material is not exceeded. Refer to glove supplier for

information on breakthrough time for specific gloves.

Skin and body protection Suitable protective clothing.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

EPOXY PUTTYCARBUSONIC LIMITED

Revision date 21/08/21 Revision Number 1

Physical stateSolidAppearancePasteColourGrey Black

Odour Sulphurous Pungent
Odour threshold No information available

Property Values Remarks • Method

pH Not applicable.

Melting point / freezing point
Boiling point / boiling range
Flash point
Evaporation rate
Flammability (solid, gas)
Not applicable.
No data available
No data available
No data available

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapour pressureNo data availableRelative vapour densityNo data available

Relative density 2.25

Water solubility
Solubility(ies)
Partition coefficient
Autoignition temperature
Insoluble in water
No data available
No data available

Decomposition temperature 150

Kinematic viscosityNo data availableDynamic viscosityNo data availableExplosive propertiesNo data availableOxidising propertiesNo data available

9.2. Other information

Solid content (%)

VOC Content (%)

Density

No information available

No information available

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical None.

mpact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoidNone known based on information supplied.

10.5. Incompatible materials

EPOXY PUTTYCARBUSONIC LIMITED

Revision date 21/8/2021 Revision Number 1

Drawn stille materials Chang saids Chang bean Chang saiding angets

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation May cause irritation of respiratory tract.

Eye contact Irritating to eyes. Causes serious eye irritation.

Skin contact May cause sensitisation by skin contact. Specific test data for the substance or mixture

is not available. Repeated or prolonged skin contact may cause allergic reactions with

susceptible persons. (based on components). Causes skin irritation.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes.

Numerical measures of toxicity

Acute toxicity

Component Information

	Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
ĺ	Bisphenol-A-Epichlorhydrin	LD50 (Rattus) > 2000 mg/kg	>2000 mg/Kg (Rattus)	
	Epoxy resin <= 700 MW	OECD 420		
	25068-38-6			

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitisation May cause sensitisation by skin contact.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicityBased on available data, the classification criteria are not met.

EPOXY PUTTYCARBUSONIC LIMITED

Revision date 20/8/2021 Revision Number 1

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
Bisphenol-A-Epichlorhy	EC50 (72h) =	1.2 mg/l 96Hr	-	2.7 mg/l 48hr		
drin Epoxy resin <=	9.4 mg/L	(Oncorhynchus		Daphia Magna		
700 MW	(Scenedesmus	mykiss)				
25068-38-6	capricornutum)					
	EPA-660/3-75-0					
	09					

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Bisphenol-A-Epichlorhydrin Epoxy resin	3.26	31
<= 700 MW 25068-38-6		

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessmentThe components in this formulation do not meet the criteria for classification as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	The substance is not PBT / vPvB

12.6. Other adverse effects

Other adverse effects No information available.

Endocrine Disruptor Information

Chemical name	EU - Endocrine Disrupters	EU - Endocrine Disruptors -
---------------	---------------------------	-----------------------------

EPOXY PUTTYCARBUSONIC LIMITED

Revision date 20/8/2021 Revision Number 1

	Candidate List	Evaluated Substances
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	Group III Chemical	-

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of contents/container in accordance with local, regional, national, and

international regulations as applicable.

Contaminated packaging

Do not reuse empty containers. Handle contaminated packages in the same way as the

product itself.

Other information

Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1UN number or ID numberNot regulated14.2Proper Shipping NameNot regulated14.3Transport hazard class(es)Not regulated14.4Packing groupNot regulated14.5Environmental hazardsNot applicable14.6Special ProvisionsNone

14.1 UN number or ID number
14.2 Proper Shipping Name
14.3 Transport hazard class(es)
14.4 Packing group
14.5 Marine pollutant
Not regulated
Not regulated
Not regulated
Not regulated
Not regulated

14.5 Marine pollutant
14.6 Special Provisions

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

None

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable

14.6 Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

EPOXY PUTTYCARBUSONIC LIMITED

Revision date 20/8/2021 Revision Number 1

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H411 - Toxic to aquatic life with long lasting effects

H412 - Harmful to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Limit Value
* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 30-Nov-2020

Indication of changes

EPOXY PUTTYCARBUSONIC LIMITED

Revision date 20/8/2021 Revision Number 1

Revision note Not applicable.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet CARBUSONIC LIMITED UK